SPECIFICATION SHEET



PRODUCT SPECIFICATION

Wattage (W) 320 Voltage (V) 24 Dimmable DALI / 1 /0-10v Dimensions (mm) 360 x 40 x 32 **Current (DC)** 13.3A Input Voltage (AC) 220 / 240 AC **Input Current** 1.6A @ 230V **Inrush Current** 80A / 230V **IP Rating** 20 50 / 60hz **Input Frequency Power Factor** >0.95 Weight 630g Min. Operating Temp. -20°C 50°C Max. Operating Temp.


DESCRIPTION

The 320W Dali is a constant voltage mode output LED driver.


This driver complies with DALI standard protocol IEC 62386, and provides multiple dimming functions:

- Active Signal
- PWM
- Adjustable resistance
- Touch DIM

DIMENSIONS (mm)



WIRING DIAGRAM



CAUTIONS A



- This product should be installed by qualified personnel.
- This product is non waterproof, need to avoid sun and rain. In case of outdoor use, please ensure it is mounted in a water proof enclosure.
- Good heat dissipation conditions extend product life. Please install the product in a well-ventilated environment.
- Please make sure LED power supply output voltage, current is used to meet the product requirements.
- Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- Due to safety concerns, PVC or rubber cord of 0.75- 1.5mm² is recommended for input and output terminal(s)(excluding signal terminals). Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- In case of malfunction, do not repair it yourself.