## **SPECIFICATION SHEET**



#### **PRODUCT SPECIFICATION**

## Current (DC) 1.65A Input Voltage (AC) 220 / 240 AC **Input Current** 0.27A @ 230V **Inrush Current** 28A / 230V 20 **IP Rating** 50 / 60hz **Input Frequency Power Factor** >0.95 Weight 151g Min. Operating Temp. -20°C 50°C Max. Operating Temp.


## **DESCRIPTION**

The 40W Dali is a constant Voltage output mode LED driver.


Support DALI dimming function, Touch DIM (Push DIM) function, 0/1-10V Dimming function.
The output and dimming circuit are also completely in

circuit are also completely in accordance with the new regulations with isolation to ensure the users and luminaire system during installation.

# DIMENSIONS (mm)



#### **WIRING DIAGRAM**



# CAUTIONS A

- This product should be installed by qualified personnel.
- This product is non waterproof, need to avoid sun and rain. In case of outdoor use, please ensure it is mounted in a water proof enclosure.
- Good heat dissipation conditions extend product life. Please install the product in a well-ventilated environment.
- Please make sure LED power supply output voltage, current is used to meet the product requirements.
- Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- Due to safety concerns, PVC or rubber cord of 0.75- 1.5mm<sup>2</sup> is recommended for input and output terminal(s) (excluding signal terminals). Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- In case of malfunction, do not repair it yourself.